


## Mod. 10840.B D5

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Mobile armoury case for rifles. Self-oiling free running wheels. Removable lid. 12 heavy duty metal latches.



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |         |
|-----------------|---------|
| <b>L LENGTH</b> | 1080 mm |
| <b>W WIDTH</b>  | 620 mm  |
| <b>D DEPTH</b>  | 400 mm  |
| <b>LID</b>      | 200 mm  |
| <b>BASE</b>     | 200 mm  |


#### EXTERNAL DIMENSIONS

|                 |         |
|-----------------|---------|
| <b>L LENGTH</b> | 1178 mm |
| <b>W WIDTH</b>  | 718 mm  |
| <b>D DEPTH</b>  | 427 mm  |

#### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 19.80 Kg             |
| <b>WEIGHT WITH FOAM</b>        | 26.30 Kg             |
| <b>WEIGHT WITH CUSTOM FOAM</b> | 25 Kg                |
| <b>VOLUME</b>                  | 260 lt               |
| <b>BUOYANCY</b>                | 120.60 Kg/max        |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 42 1/2 in  |
| <b>W WIDTH</b>  | 24 7/16 in |
| <b>D DEPTH</b>  | 15 3/4 in  |
| <b>LID</b>      | 7 7/8 in   |
| <b>BASE</b>     | 7 7/8 in   |

#### EXTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L LENGTH</b> | 46 3/8 in   |
| <b>W WIDTH</b>  | 28 1/4 in   |
| <b>D DEPTH</b>  | 16 13/16 in |

#### OTHER DATA

|                                |                         |
|--------------------------------|-------------------------|
| <b>WEIGHT EMPTY</b>            | 43.65 lbs               |
| <b>WEIGHT WITH FOAM</b>        | 57.32 lbs               |
| <b>WEIGHT WITH CUSTOM FOAM</b> | 55.11 lbs               |
| <b>VOLUME</b>                  | 68.68 gal               |
| <b>BUOYANCY</b>                | 265.87 lbs/max          |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max +194 |