

## Mod. 13513.DCV

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Large rifle cases ideal for carrying long rifles and accessories. Optional shoulder strap. Wheels with bearings. Available in black, olive drab and desert tan colors. OEM colors on demand.



#### METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |         |
|-----------------|---------|
| <b>L LENGTH</b> | 1350 mm |
| <b>W WIDTH</b>  | 350 mm  |
| <b>D DEPTH</b>  | 135 mm  |
| <b>LID</b>      | 42 mm   |
| <b>BASE</b>     | 93 mm   |


#### EXTERNAL DIMENSIONS

|                 |         |
|-----------------|---------|
| <b>L LENGTH</b> | 1430 mm |
| <b>W WIDTH</b>  | 415 mm  |
| <b>D DEPTH</b>  | 159 mm  |

#### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 8.70 Kg              |
| <b>WEIGHT WITH FOAM</b>        | 9.95 Kg              |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                   |
| <b>VOLUME</b>                  | 63.70 lt             |
| <b>BUOYANCY</b>                | 39.50 Kg/max         |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

#### IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 53 1/8 in  |
| <b>W WIDTH</b>  | 13 3/4 in  |
| <b>D DEPTH</b>  | 5 5/16 in  |
| <b>LID</b>      | 1 5/8 in   |
| <b>BASE</b>     | 3 11/16 in |

#### EXTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 56 5/16 in |
| <b>W WIDTH</b>  | 16 5/16 in |
| <b>D DEPTH</b>  | 6 1/4 in   |

#### OTHER DATA

|                                |                         |
|--------------------------------|-------------------------|
| <b>WEIGHT EMPTY</b>            | 19.18 lbs               |
| <b>WEIGHT WITH FOAM</b>        | 21.93 lbs               |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                     |
| <b>VOLUME</b>                  | 16.82 gal               |
| <b>BUOYANCY</b>                | 87.08 lbs/max           |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max +194 |