

**Mod. 3815HL.G E**

3815HL – EXPLORER CASES, ULTRALIGHT WATERPROOF CASE


Medium size watertight case injected with proprietary copolymer PP that makes it more resistant and lightweight than other similar products. IP67 and MIL Stan certified\* to be resistant to impact, liquids, shocks. Ideal container for documents, laptops, books, medical equipment and electronic devices, tools and more.

- Metal reinforced padlock holes
- Single block high performance injected O-ring
- Automatic pressure valve
- Soft rubber handle grip
- Removable lid
- Anti-tilt support
- Certified to grant constant performances between -33°C and +90 °C.
- Six standard colors available

\*Pending certification release



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 380 mm |
| <b>W</b> WIDTH  | 270 mm |
| <b>D</b> DEPTH  | 155 mm |
| <b>LID</b>      | 47 mm  |
| <b>BASE</b>     | 108 mm |


#### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 420 mm |
| <b>W</b> WIDTH  | 340 mm |
| <b>D</b> DEPTH  | 177 mm |

#### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 2.20 Kg              |
| <b>WEIGHT WITH FOAM</b>        | 2.53 Kg              |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                   |
| <b>VOLUME</b>                  | 15.90 lt             |
| <b>BUOYANCY</b>                | 10 Kg/max            |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L</b> LENGTH | 14 15/16 in |
| <b>W</b> WIDTH  | 10 5/8 in   |
| <b>D</b> DEPTH  | 6 1/8 in    |
| <b>LID</b>      | 1 7/8 in    |
| <b>BASE</b>     | 4 1/4 in    |

#### EXTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L</b> LENGTH | 16 9/16 in |
| <b>W</b> WIDTH  | 13 3/8 in  |
| <b>D</b> DEPTH  | 6 15/16 in |

#### OTHER DATA

|                                |                         |
|--------------------------------|-------------------------|
| <b>WEIGHT EMPTY</b>            | 4.85 lbs                |
| <b>WEIGHT WITH FOAM</b>        | 5.57 lbs                |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                     |
| <b>VOLUME</b>                  | 4.20 gal                |
| <b>BUOYANCY</b>                | 22.04 lbs/max           |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max +194 |