# Mod. 3818.B E


COPOLYMER POLYPROPYLENE WATERPROOF CASE

Medium size case with jam-free purge valve and latches. Soft grip rubber handle reinforced with corrosion proof steel pins. Panel mounting bracket slots.






METRIC MM-KG-C°





| INTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 380 mm |
| W WIDTH | 270 mm |
| D DEPTH | 180 mm |
| LID | 47 mm |
| BASE | 133 mm |

| EXTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 410 mm |
| W WIDTH | 340 mm |
| D DEPTH | 205 mm |

| OTHER DATA | |
|---|---|
| WEIGHT EMPTY | 3.14 Kg |
| WEIGHT WITH FOAM | 3.58 Kg |
| WEIGHT WITH CUSTOM FOAM | Kg |
| VOLUME | 18.40 lt |
| BUOYANCY | 12.40 Kg/max |
| OPERATING TEMPERATURE | °C min '-33 / max '+90 |

IMPERIAL IN-LBS-F°




| INTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 14 15/16 in |
| W WIDTH | 10 5/8 in |
| D DEPTH | 7 1/16 in |
| LID | 1 7/8 in |
| BASE | 5 1/4 in |

| EXTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 16 1/8 in |
| W WIDTH | 13 3/8 in |
| D DEPTH | 8 1/16 in |

| OTHER DATA | |
|---|---|
| WEIGHT EMPTY | 6.92 lbs |
| WEIGHT WITH FOAM | 7.89 lbs |
| WEIGHT WITH CUSTOM FOAM | lbs |
| VOLUME | 4.75 gal |
| BUOYANCY | 27.33 lbs/max |
| OPERATING TEMPERATURE | °F min '-27.4 / max '+194 |