Mod. 4419HL.O E

4419HL – EXPLORER CASES, ULTRALIGHT WATERPROOF CASE


Medium size watertight case, injected with proprietary copolymer PP that makes it more resistant and lightweight than other similar products. IP67 and MIL Stan certified to be resistant to impact, liquids, shocks.
Ideal container for mechanical equipment, optical equipment and electronic devices, valuables, outdoor equipment and more. Can be used as a portable work station.

- Metal reinforced padlock holes
- Single block high performance injected O-ring
- Automatic pressure valve
- Soft rubber handle grip
- Removable lid
- Anti-tilt support
- Certified to grant constant performances between -33°C and +90 °C.
- Six standard colors available





METRIC MM-KG-C°



INTERNAL DIMENSIONS	
L LENGTH	445 mm
W WIDTH	345 mm
D DEPTH	190 mm
LID	47 mm
BASE	143 mm


EXTERNAL DIMENSIONS	
L LENGTH	485 mm
W WIDTH	414 mm
D DEPTH	212 mm

OTHER DATA	
WEIGHT EMPTY	2.91 Kg
WEIGHT WITH FOAM	3.58 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	29.2 lt
BUOYANCY	19.8 Kg/max
OPERATING	°C min -33 / max +90

EXPLORER CASES BY GT LINE SRL VIA DEL LAVORO, 9 LOC. CRESPELLANO - 40053 VALSAMOGGIA(BOLOGNA)-ITALY - TELEPHONE +39/051/65041 - FAX +39/051/734925
WWW.EXPLORERCASES.COM

TEMPERATURE

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS	
L LENGTH	17 1/2 in
W WIDTH	13 9/16 in
D DEPTH	7 1/2 in
LID	1 7/8 in
BASE	5 5/8 in

EXTERNAL DIMENSIONS	
L LENGTH	19 1/8 in
W WIDTH	16 5/16 in
D DEPTH	8 3/8 in

OTHER DATA	
WEIGHT EMPTY	6.41 lbs
WEIGHT WITH FOAM	7.89 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	7.71 gal
BUOYANCY	43.65 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max +194