## Mod. 4820HL.D E

4820HL – EXPLORER CASES, ULTRALIGHT WATERPROOF CASE


Medium size watertight case, injected with proprietary copolymer PP that makes it more resistant and lightweight than other similar products. IP67 and MIL Stan certified to be resistant to impact, liquids, shocks. Ideal container for travel gear, photographic and video equipment, valuables, outdoor equipment and more.

•Metal reinforced padlock holes
•Single block high performance injected O-ring
•Automatic pressure valve
•Soft rubber handle grip
•Certified to grant constant performances between -33°C and +90 °C.
•Six standard colors available





METRIC MM-KG-C°





| INTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 480 mm |
| W WIDTH | 370 mm |
| D DEPTH | 205 mm |
| LID | 50 mm |
| BASE | 155 mm |

| EXTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 520 mm |
| W WIDTH | 440 mm |
| D DEPTH | 230 mm |

| OTHER DATA | |
|---|---|
| WEIGHT EMPTY | 3.41 Kg |
| WEIGHT WITH FOAM | 4.17 Kg |
| WEIGHT WITH CUSTOM FOAM | Kg |
| VOLUME | 36.40 lt |
| BUOYANCY | 24.80 Kg/max |
| OPERATING TEMPERATURE | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°




| INTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 18 7/8 in |
| W WIDTH | 14 9/16 in |
| D DEPTH | 8 1/16 in |
| LID | 1 15/16 in |
| BASE | 6 1/8 in |

| EXTERNAL DIMENSIONS | |
|---|---|
| L LENGTH | 20 1/2 in |
| W WIDTH | 17 5/16 in |
| D DEPTH | 9 1/16 in |

| OTHER DATA | |
|---|---|
| WEIGHT EMPTY | 7.51 lbs |
| WEIGHT WITH FOAM | 9.19 lbs |
| WEIGHT WITH CUSTOM FOAM | lbs |
| VOLUME | 9.61 gal |
| BUOYANCY | 54.67 lbs/max |
| OPERATING TEMPERATURE | °F min -27.4 / max +194 |