Mod. 5140.B.6U

WATERPROOF RACK MOUNT CASE

6U rack-size waterproof case.
Units can fit horizontally in the front side of the case, or vertically from the top of the case.
Practical lightweight and economical solutions to carry small rack devices up to 6U (units).
This case can be used in horizontal mode up to 6U or in vertical mode up to 5U.
The internal hardware can easily be reconfigured for either ones of the two versions.
Handles on both side and wheels plus trolley handle in the rear allow for a practical carrying of this case.
The provided M6 Cage Nuts and screws grants practical mounting of any device.

HORIZONTAL USE
RACK DEPTH: 265 mm (245 mm if backward positioning)
FRONT LID DEPTH: 20 mm (40 mm if backward positioning)

VERTICAL USE
RACK DEPTH: 325 mm (385 mm if forward positioning)
UPPER LID DEPTH: 75 mm (15 mm if forward positioning)


HORIZONTAL USE



VERTICAL USE




METRIC MM-KG-C°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	mm	L LENGTH	581 mm	WEIGHT EMPTY	9.2 Kg
W WIDTH	mm	W WIDTH	381 mm	WEIGHT WITH FOAM	Kg
D DEPTH	mm	D DEPTH	455 mm	WEIGHT WITH CUSTOM FOAM	Kg
LID	mm			VOLUME	lt
BASE	mm			BUOYANCY	Kg/max
				OPERATING TEMPERATURE	°C min -33 / max 90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	in	L LENGTH	22 7/8 in	WEIGHT EMPTY	20.28 lbs
W WIDTH	in	W WIDTH	15 in	WEIGHT WITH FOAM	lbs
D DEPTH	in	D DEPTH	17 15/16 in	WEIGHT WITH CUSTOM FOAM	lbs
LID	in			VOLUME	gal
BASE	in			BUOYANCY	lbs/max
				OPERATING TEMPERATURE	°F min -27.4 / max 194