

**Mod. 5140X.B.5AL****COPOLYMER POLYPROPYLENE WATERPROOF CONTAINER**

Polypropylene waterproof containers with extractable drawers. This trolley is specifically engineered for the professionals who need to carry a variety of tools and spare components. Pivoting wheels on demand.


**THIS PRODUCT IS POWERED BY INTELLIRESPOND, the free App that allows for personal tool inventory and control of the content. Please visit [www.intellirespond.com](http://www.intellirespond.com)**



5 x AIBOX3.E (H30 mm - 1.2 in)  
1 x AIBOX6.E (H60 mm - 2.4 in)  
**BLACK BOXES EMPTY**



METRIC MM-KG-C°

**INTERNAL DIMENSIONS**

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 516 mm |
| <b>W</b> WIDTH  | 296 mm |
| <b>D</b> DEPTH  | 402 mm |
| <b>LID</b>      | mm     |
| <b>BASE</b>     | mm     |


**EXTERNAL DIMENSIONS**

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 581 mm |
| <b>W</b> WIDTH  | 381 mm |
| <b>D</b> DEPTH  | 455 mm |

**OTHER DATA**

|                           |                      |
|---------------------------|----------------------|
| <b>WEIGHT EMPTY</b>       | 9.75 Kg              |
| <b>WEIGHT WITH FOAM</b>   | Kg                   |
| <b>WEIGHT WITH CUSTOM</b> | Kg                   |
| <b>FOAM</b>               |                      |
| <b>VOLUME</b>             | lt                   |
| <b>BUOYANCY</b>           | Kg/max               |
| <b>OPERATING</b>          | °C min -33 / max +90 |
| <b>TEMPERATURE</b>        |                      |

IMPERIAL IN-LBS-F°



# INTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L</b> LENGTH | 20 5/16 in  |
| <b>W</b> WIDTH  | 11 5/8 in   |
| <b>D</b> DEPTH  | 15 13/16 in |
| LID             | in          |
| BASE            | in          |

# EXTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L</b> LENGTH | 22 7/8 in   |
| <b>W</b> WIDTH  | 15 in       |
| <b>D</b> DEPTH  | 17 15/16 in |

# OTHER DATA

|                    |                    |
|--------------------|--------------------|
| WEIGHT EMPTY       | 21.49 lbs          |
| WEIGHT WITH FOAM   | lbs                |
| WEIGHT WITH CUSTOM | lbs                |
| FOAM               |                    |
| VOLUME             | gal                |
| BUOYANCY           | lbs/max            |
| OPERATING          | °F min -27.4 / max |
| TEMPERATURE        | +194               |