


## Mod. 5221HL.D

5221HL – EXPLORER CASES, ULTRALIGHT COPOLYMER POLYPROPYLENE WATERPROOF CASE

Heavy duty cases with wheels with ball bearings and telescopic handle. Sealing o-ring and removable lid. Available empty or with layers of pre-cubed foam in the bottom and convoluted foam in the lid.



METRIC MM-KG-C°



### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 520 mm |
| <b>W WIDTH</b>  | 285 mm |
| <b>D DEPTH</b>  | 205 mm |
| <b>LID</b>      | 55 mm  |
| <b>BASE</b>     | 150 mm |


### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 550 mm |
| <b>W WIDTH</b>  | 350 mm |
| <b>D DEPTH</b>  | 225 mm |

### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 3.90 Kg              |
| <b>WEIGHT WITH FOAM</b>        | 4.50 Kg              |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                   |
| <b>VOLUME</b>                  | 30.3 lt              |
| <b>BUOYANCY</b>                | 20 Kg/max            |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°



### INTERNAL DIMENSIONS

|                 |           |
|-----------------|-----------|
| <b>L LENGTH</b> | 20 1/2 in |
| <b>W WIDTH</b>  | 11 1/4 in |
| <b>D DEPTH</b>  | 8 1/16 in |
| <b>LID</b>      | 2 3/16 in |
| <b>BASE</b>     | 5 7/8 in  |

### EXTERNAL DIMENSIONS

|                 |           |
|-----------------|-----------|
| <b>L LENGTH</b> | 21 5/8 in |
| <b>W WIDTH</b>  | 13 3/4 in |
| <b>D DEPTH</b>  | 8 7/8 in  |

### OTHER DATA

|                                |                    |
|--------------------------------|--------------------|
| <b>WEIGHT EMPTY</b>            | 8.59 lbs           |
| <b>WEIGHT WITH FOAM</b>        | 9.92 lbs           |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                |
| <b>VOLUME</b>                  | 8 gal              |
| <b>BUOYANCY</b>                | 44.09 lbs/max      |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max |

---

TEMPERATURE

+194