# Mod. 5822.B


COPOLYMER POLYPROPYLENE WATERPROOF CASE

Watertight cases offer absolute protection in the harshest environment for all kinds of sensitive instrumentation. Practical side handles and padlockable points.






METRIC MM-KG-C°




| INTERNAL DIMENSIONS | | EXTERNAL DIMENSIONS | | OTHER DATA | |
|---|---|---|---|---|---|
| L LENGTH | 580 mm | L LENGTH | 650 mm | WEIGHT EMPTY | 7.16 Kg |
| W WIDTH | 440 mm | W WIDTH | 510 mm | WEIGHT WITH FOAM | 8.39 Kg |
| D DEPTH | 220 mm | D DEPTH | 245 mm | WEIGHT WITH CUSTOM FOAM | Kg |
| LID | 60 mm | | | VOLUME | 56.10 lt |
| BASE | 160 mm | | | BUOYANCY | 36.70 Kg/max |
| | | | | OPERATING TEMPERATURE | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°




| INTERNAL DIMENSIONS | | EXTERNAL DIMENSIONS | | OTHER DATA | |
|---|---|---|---|---|---|
| L LENGTH | 22 13/16 in | L LENGTH | 25 9/16 in | WEIGHT EMPTY | 15.78 lbs |
| W WIDTH | 17 5/16 in | W WIDTH | 20 1/16 in | WEIGHT WITH FOAM | 18.49 lbs |
| D DEPTH | 8 11/16 in | D DEPTH | 9 5/8 in | WEIGHT WITH CUSTOM FOAM | lbs |
| LID | 2 3/8 in | | | VOLUME | 14.79 gal |
| BASE | 6 5/16 in | | | BUOYANCY | 80.90 lbs/max |
| | | | | OPERATING TEMPERATURE | °F min -27.4 / max +194 |