Mod. 5822.O E


COPOLYMER POLYPROPYLENE WATERPROOF CASE

Watertight cases offer absolute protection in the harshest environment for all kinds of sensitive instrumentation. Practical side handles and padlockable points.





METRIC MM-KG-C°




INTERNAL DIMENSIONS	
L LENGTH	580 mm
W WIDTH	440 mm
D DEPTH	220 mm
LID	60 mm
BASE	160 mm

EXTERNAL DIMENSIONS	
L LENGTH	650 mm
W WIDTH	510 mm
D DEPTH	245 mm

OTHER DATA	
WEIGHT EMPTY	7.16 Kg
WEIGHT WITH FOAM	8.39 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	56.10 lt
BUOYANCY	36.70 Kg/max
OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS	
L LENGTH	22 13/16 in
W WIDTH	17 5/16 in
D DEPTH	8 11/16 in
LID	2 3/8 in
BASE	6 5/16 in

EXTERNAL DIMENSIONS	
L LENGTH	25 9/16 in
W WIDTH	20 1/16 in
D DEPTH	9 5/8 in

OTHER DATA	
WEIGHT EMPTY	15.78 lbs
WEIGHT WITH FOAM	18.49 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	14.79 gal
BUOYANCY	80.90 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max +194